

Name Kassettenband	Größe	Länge	Artikelnummer	Temperaturbeständigkeit
IND Permanent Vinyl				
Permanent Vinyl Black on White	9 mm	5,5 m	18443	-40°C to 80°C
Permanent Vinyl White on Black	9 mm	5,5 m	1805437	-40°C to 80°C
Permanent Vinyl Black on White	12 mm	5,5 m	18444	-40°C to 80°C
Permanent Vinyl Black on Yellow	12 mm	5,5 m	18432	-40°C to 80°C
Permanent Vinyl Black on Orange	12 mm	5,5 m	18435	-40°C to 80°C
Permanent Vinyl Black on Grey	12 mm	5,5 m	1805413	-40°C to 80°C
Permanent Vinyl White on Red	12 mm	5,5 m	1805416	-40°C to 80°C
Permanent Vinyl White on Black	12 mm	5,5 m	1805435	-40°C to 80°C
Permanent Vinyl White on Green	12 mm	5,5 m	1805414	-40°C to 80°C
Permanent Vinyl White on Blue	12 mm	5,5 m	1805243	-40°C to 80°C
Permanent Vinyl Black on White	19 mm	5,5 m	18445	-40°C to 80°C
Permanent Vinyl Black on Yellow	19 mm	5,5 m	18433	-40°C to 80°C
Permanent Vinyl Black on Orange	19 mm	5,5 m	18436	-40°C to 80°C
Permanent Vinyl White on Red	19 mm	5,5 m	1805422	-40°C to 80°C
Permanent Vinyl White on Black	19 mm	5,5 m	1805436	-40°C to 80°C
Permanent Vinyl White on Green	19 mm	5,5 m	1805420	-40°C to 80°C
Permanent Vinyl White on Blue	19 mm	5,5 m	1805417	-40°C to 80°C
Permanent Vinyl Black on White	24 mm	5,5 m	1805430	-40°C to 80°C
Permanent Vinyl Black on Yellow	24 mm	5,5 m	1805431	-40°C to 80°C
IND Permanent Polyester				
Permanent Polyester Black on White	6 mm	5,5 m	1805442	-40°C to 80°C
Permanent Polyester Black on Clear	6 mm	5,5 m	1805440	-40°C to 80°C
Permanent Polyester Black on Metallic	6 mm	5,5 m	1805441	-40°C to 80°C
Permanent Polyester Black on White	9 mm	5,5 m	18482	-40°C to 80°C
Permanent Polyester Black on Clear	9 mm	5,5 m	18508DMO	-40°C to 80°C
Permanent Polyester Black on Metallic	9 mm	5,5 m	18485	-40°C to 80°C
Permanent Polyester Black on White	12 mm	5,5 m	18483	-40°C to 80°C
Permanent Polyester Black on Clear	12 mm	5,5 m	622289	-40°C to 80°C
Permanent Polyester Black on Metallic	12 mm	5,5 m	18486	-40°C to 80°C
Permanent Polyester Black on White	19 mm	5,5 m	18484	-40°C to 80°C
Permanent Polyester Black on Clear	19 mm	5,5 m	622290	-40°C to 80°C
Permanent Polyester Black on Metallic	19 mm	5,5 m	18487	-40°C to 80°C
Permanent Polyester Black on White	24 mm	5,5 m	1734523	-40°C to 80°C
IND Flexible Nylon				
Flexible Nylon Black on White	12 mm	3,5 m	18488	-40°C to 60°C
Flexible Nylon Black on Yellow	12 mm	3,5 m	18490	-40°C to 60°C
Flexible Nylon Black on White	19 mm	3,5 m	18489	-40°C to 60°C
Flexible Nylon Black on Yellow	19 mm	3,5 m	18491	-40°C to 60°C
Flexible Nylon Black on White	24 mm	3,5 m	1734524	-40°C to 60°C
Flexible Nylon Black on Yellow	24 mm	3,5 m	1734525	-40°C to 60°C
IND Schrumpfschlauch-Bänder				
Heat-Shrink Tube Black on White	6 mm	1,5 m	18051	-55°C to 135°C
Heat-Shrink Tube Black on Yellow	6 mm	1,5 m	18052	-55°C to 135°C
Heat-Shrink Tube Black on White	9 mm	1,5 m	18053	-55°C to 135°C
Heat-Shrink Tube Black on Yellow	9 mm	1,5 m	18054	-55°C to 135°C
Heat-Shrink Tube Black on White	12 mm	1,5 m	18055	-55°C to 135°C
Heat-Shrink Tube Black on Yellow	12 mm	1,5 m	18056	-55°C to 135°C
Heat-Shrink Tube Black on White	19 mm	1,5 m	18057	-55°C to 135°C
Heat-Shrink Tube Black on Yellow	19 mm	1,5 m	18058	-55°C to 135°C
Heat-Shrink Tube Black on White	24 mm	1,5 m	1805443	-55°C to 135°C
IND Embossing				
Non-Adhesive Stainless Steel	12 mm	6,40 m	32500	up to 1300°C
Non-Adhesive Aluminum	12 mm	4,88 m	31000	up to 250°C
Adhesive Aluminum	12 mm	3,66 m	35800	up to 250°C